# Manual Bulk Models



## **Trigger-Actuated Hi-Thrust Drives**



### **Availability and Ordering Information:**

- All Albion SPECIAL DELUXE Models are available with either C1100 ULTRA or C700 SDLplus Hi-Thrust Drives.
- All Albion UTILITY Models are available with C600 UTILITYplus Hi-Thrust Drive.
- For model numbers and pricing, please refer to current Albion price sheets.
- For additional information, or to place an order, contact your Albion Customer Service Rep.

## ULTRA Models Patented with C1100 Hi-Thrust Drive

### Two operating speeds.

High power/low displacement or low power/high displacement. Quick change to second speed for longer stroke, less power.

#### FFATURES:

- ✓Develops up to 1100 lbs of thrust, equivalent to 3½" dia air-powered models at 120 psi
- ✓ Precision machined, wear-resistant parts for reliable Hi-Thrust dispensing
- Specially designed recoil for easy release under extreme pressure
- ✓Dent-resistant rod…hardened, ground and polished

## SDLplus Models with C700 Hi-Thrust Drive

Almost **twice** the thrust of our standard Special Deluxe drive with minimal added cost.

#### **FEATURES:**

- Same quality construction and features as our Special Deluxe Drive
- Develops up to 700 lbs of thrust, equivalent to 2¾" dia air-powered models at 120 psi
- Strengthened double-grip recoil mechanism to handle heavier loads

## **UTILITY**plus with C600 Hi-Thrust Drive

Almost **twice** the thrust of our standard Utility Drive with minimal added cost.

#### **FEATURES:**

- Same durable construction and features as our standard Utility Drive
- ✓ Develops up to 600 lbs of thrust
- **✓**ALBION QUALITY

\*Thrust values are based upon the hand dynamometer strength of an average male in the USA holding the tool in it's normal grip area.

## **SPECIAL DELUXE**



The Professional' Choice



DESCRIPTION CAPACITY CHAMBER WT (lb) DL-59-T13\*† Increased capacity minimizes reloading. 2"D x 18"L 1 quart 5 Best price/performance 1 qt model. DL-59C-T13† Fast action clip-on cap. 2"D x 18"L 1 quart DL-59-T17\* Includes rolled thread screw-on ring cap 1 quart 2"D x 18"L and three 235-3 plastic cone nozzles. General purpose. Our most popular model. DL-45-T13\*† 1½ pint 2"D x 14"L 4 DL-45C-T13<sup>†</sup> Fast action clip-on cap. 1½ pint 2"D x 14"L DL-45-T17\* Includes rolled thread screw-on ring cap 1½ pint 2"D x 14"L and three 235-3 plastic cone nozzles. 770-20 Full-barrel with reducer, 2" ring cap 1 quart 2%"D x 12"L 4.5 and 235-3 nozzle for confined areas. 103-15 JUMBO diameter. High volume, lower density. 2½ quart 3%"D x 16"L Supplied with 3/4" diameter metal 32-35 nozzle.

Albion Special Deluxe manual drive bulk models are designed for today's higher viscosity materials and the demands of cold weather use.

#### FEATURES:

- ✓ Reinforced construction for high-pressure applications
- ✓ Smooth, durable finish, welded heavy gauge steel
- ✓ Epoxy-coated handle for comfort and corrosion resistance
- ✓ T-pull with 5/16" square smooth piston rod
- Swivel handle rotates, allowing for easy change of direction and uninterrupted flow

When extruding a high volume of stiff material, ULTRA or Air-Powered models are recommended over Special Deluxe models 770 and 103.

All 2" dia models equipped with conical ejectors to squeeze out all material from chamber. All 2%" and 3%" diameter models have cut threads.

\*Quality screw-on caps with rolled threads for a tighter seal.

† Includes 1/2" diameter metal 32-55 nozzle.

ALBION Engineering Co. 2080A Wheatsheaf Lane Philadelphia, PA 19124-5091 USA 215-535-3476

FAX TOLL-FREE 800-841-7132 USA • CANADA • PUERTO RICO US VIRGIN ISLANDS ALL OTHERS INTERNATIONAL FAX 001-215-744-4719

**E-MAIL** service@albioneng.com

Check our Web Site for new items!

www.albioneng.com



## Manual Bulk Models Catalog 255B





MODEL	DESCRIPTION	CAPACITY	CHAMBER	WT (lb)
DL-45-01	Large volume.	1½ pint	2"D x 14"L	3.75
DL-32-01	Low volume.	1 pint	2"D x 10½"L	3.25
DL-810-01*	CONVERTIBLE GUN. Assembled with ejector for 1/2 or 1/10 gallon cartridge.	1/8 gallon	2"D x 10½"L	3.25
DL-24C*	CONVERTIBLE GUN. Assembled with ejector for 1/10 gallon cartridge.	⅓₀ gallon	2"D x 9"L	3.25
46-9A	Compact. Features counter-balancing knob-pull.	⅓₀ gallon	2"D x 9"L	3.75

All models supplied with metal 32-88 nozzle (3/8" dia). DL24C and 46-9A have fast action clip-on cap. All others have screw-on type

\*Includes leather piston cups for bulk conversion.



Albion Deluxe manual drive bulk models are built for daily heavy-duty use, and offer the best combination of price and performance.

- ✓ ¼" square smooth piston rod that rotates for 4 times longer life.
- ✓ Thumb-activated instant pressure release
- ✔ Formed steel construction and corrosion resistant zinc plating
- ✓ Solvent resistant piston
- ✓ User can regulate stroke to fit hand size
- ✓ Swivel handle rotates, allowing for easy change of direction and uninterrupted flow



MODEL	DESCRIPTION	CAPACITY	CHAMBER	WT (lb)
50-9	Large volume.	1½ pint	2"D x 14"L	3.75
50-1	Convertible. Assembled for 1/10 gallon cartridges.	¹⁄₁₀ gallon	2"D x 9"L	3

Albion's Utility manual drive bulk models are built for moderate use and are more durable than the average professional tool.

- √ 5/16" round smooth piston rod
- ✓ Heavy gauge steel and zinc plating
- ✓ Fast acting, 3-prong clip-on cap
- ✓ Easy to clean plastic nozzle and piston
- ✓ Durable coil springs
- ALBION QUALITY

## Try Albion's 800 Series Barrel Brush to clean your gun. Ask for Catalog 265.

## **Application Information:**

1. Converting from bulk to hard cartridge

Any 2" or 25%" model. Replace bulk piston with flat disc piston (ejector):

All 2": Part No. 29-5. All 2%": Part No. 29-G12.

NOTE: With unspouted cartridge, hold forward against front cap with spring or spacer assembly.

2. Converting from bulk to sausage-pack

Any 2" dia bulk model convertible to sausage-pack with piston assembly replacement: Teflon type: Kit 47-42. Finger type: Kit 47-23.

Not recommended for repeated use. Bulk residue left in barrel or on piston packing will prevent skin on sausage-pack from folding up properly.

3. Piston packing options for specific applications (leather is standard equipment)

LEATHER: Low friction. Excellent chemical resistance. Handles wide range of materials. Clean and oil for flex. TEFLON: Lowest friction and inert to many chemicals. Expensive, subject to wear and cold flow. NYLON: Moderate friction. Good chemical resistance. Springy. Scrapes barrel walls clean.

HYTREL: Moderate friction and good chemical resistance. Stiff and brittle. Scrapes barrel walls clean. NITRILE RUBBER: High friction. Low chemical resistance. Elastic. Recommended with water-based materials. POLY PLASTIC: Lowest cost alternative.

On Leather and Teflon only: Albion Piston Packing Expanders will extend life and reduce blow-by.

For "no-drip" performance, hook the recoil plate under the recoil lock.

### Where to find it?

**ALBION NOZZLES, CATALOG 264 ALBION SPECIAL TOOLS, CATALOG 265** ALBION ACCESSORIES, CATALOG 266 ALBION AIR-POWERED, CATALOG 260 and 261

**COPIES SENT ON REQUEST** 

**BACKED BY ALBION'S WARRANTY** AND COMMITMENT TO
PROFESSIONAL QUALITY TOOLS