

## Enviro Klean® Degreaser Cleaning Specification

*Specifier Note: The information provided below is intended to guide the Architect in developing specifications for products manufactured by PROSOCO, Inc. and should not be viewed as a complete source of information about the product(s). The Architect should always refer to the Product Data Sheet and MSDS for additional recommendations and for safety information. See also PROSOCO Section 04900 Masonry Restoration & Cleaning.*

*Specifier Note: Paragraph below is for PART 1 GENERAL, Quality Assurance.*

### Test Area

Test a minimum 4 ft. by 4 ft. area on each type of masonry. Use manufacturer's application instructions. Let the test panel dry 3 to 7 days before inspection. Keep test panels available for comparison throughout the cleaning project.

*Specifier Note: Paragraphs below are for PART 2 PRODUCTS, Manufacturers and Products.*

**Manufacturer:** PROSOCO, Inc., 3741 Greenway Circle, Lawrence, KS 66046. Phone: (800) 255-4255; Fax: (785) 830-9797. E-mail: [CustomerCare@prosoco.com](mailto:CustomerCare@prosoco.com)

### Product Description

Enviro Klean® Degreaser is a mildly alkaline solution that scours oil and grease films, adhesive tape residues and rubber tire marks and scuffs from concrete, tile and masonry floors.

Degreaser also cleans a huge range of nonmasonry surfaces including plastic, vinyl, glass, metal and fiberglass. Gets greasy smoke films and atmospheric dirt off building signs, awnings, canvas materials and tarps. Breaks the grip of salt and hard water deposits on fiberglass, chrome and painted surfaces. Works in many industrial precision-cleaning applications suitable for water-based solutions. Excellent for degreasing engines, vehicles and industrial equipment.

Effective for daily and routine maintenance cleaning when heavily diluted with water.

### Technical Data

FORM: Clear amber liquid; mild citrus odor

SPECIFIC GRAVITY: 1.03

FLASH POINT: > 200 degrees F (>93 degrees C) (ASTM D 3278)

FREEZE POINT: 19 degrees F (-7 degrees C)

WT/GAL: 8.58 lbs.

pH: 12.0 - 12.4

### Limitations

- Not for use on polished marble.

*Specifier Note: Paragraphs below are for PART 3 EXECUTION, Installation.*

### Application

Before applying, read "Protect" and "Precautionary Measures" sections in the Manufacturer's Product Data Sheet for Degreaser. Dilute Degreaser concentrate with 4-200 parts water. Refer to Product Data Sheet for recommended dilution for intended use.

1. Remove loose debris and heavy buildups using brooms, brushes or scrapers.
2. Apply diluted cleaning solution with low-pressure spray, densely filled cleaning brush or with mop. Apply liberally.
3. Let solution dwell 1-3 minutes.
4. Reapply and scrub vigorously.

5. Water rinse thoroughly to remove all residues. High-pressure rinsing improves cleaning efficiency and lessens need for scrubbing.