

## **Sure Klean<sup>®</sup> Weather Seal Natural Stone Treatment Water Repellent Specification**

*Specifier Note: The information provided below is intended to guide the Architect in developing specifications for products manufactured by PROSOCO, Inc. and should not be viewed as a complete source of information about the product(s). The Architect should always refer to the Product Data Sheet and MSDS for additional recommendations and for safety information. See also PROSOCO Section 07190 Water Repellents.*

*Specifier Note: Paragraph below is for PART 1 GENERAL, Quality Assurance.*

### **Test Area**

Test a minimum 4 ft. by 4 ft. area on each type of masonry. Use the manufacturer's application instructions. Let test area protective treatment cure before inspection. Keep test panels available for comparison throughout the protective treatment project.

*Specifier Note: Paragraphs below are for PART 2 PRODUCTS, Manufacturers and Products.*

**Manufacturer:** PROSOCO, Inc., 3741 Greenway Circle, Lawrence, KS 66046. Phone: (800) 255-4255; Fax: (785) 830-9797. E-mail: [CustomerCare@prosoco.com](mailto:CustomerCare@prosoco.com)

### **Product Description**

Sure Klean<sup>®</sup> Weather Seal Natural Stone Treatment is a modified siloxane water repellent developed for limestone, marble and most other traditional masonry surfaces. Natural Stone Treatment penetrates deeply to provide long-lasting protection without altering the natural appearance of the substrate.

Natural Stone Treatment reduces the severity of biological staining common to regions with high relative humidity. Treated surfaces resist dark staining and degradation caused by fungal growth, mold and mildew.

### **Technical Data**

FORM: Clear liquid, mild odor

ACTIVE SUBSTANCE CONTENT: 15%

SPECIFIC GRAVITY: 0.805

FLASH POINT: 118 degrees F (48 degrees C) (ASTM D 3278)

WT./GAL.: 6.70 lbs.

VOC: 732 g/L

FREEZE POINT: <-22 degrees F (<-30 degrees C)

### **Limitations**

- May damage glass or be difficult to remove. Always protect.
- Product will not compensate for structural or material defects.

*Specifier Note: Paragraphs below are for PART 3 EXECUTION, Installation.*

### **Application**

Before applying, read "Protect" and "Precautionary Measures" sections in the Manufacturer's Product Data Sheet for Weather Seal Natural Stone Treatment. Refer to the Product Data Sheet for additional information about application of Weather Seal Natural Stone Treatment. Do not alter or dilute.

### **Vertical Application Instructions**

For best results, apply protective treatment "wet-on-wet" to a thoroughly dry surface.

**Spray:** Saturate from the bottom up, creating a 6" to 8" rundown below the spray contact point. Let the first application penetrate. Resaturate within 5 minutes. Less material will be needed for the second application.

Note: When using a brush, roller or lambswool applicator, saturate the surface. Brush out heavy runs and drops that do not penetrate after a few minutes.

**Horizontal Application Instructions**

1. Saturate in a single application. Use enough to keep the surface wet for a few minutes.
2. Thoroughly broom out puddles that do not completely penetrate the surface. Soak up any remaining material with a clean towel.