

Sure Klean[®] Paver Enhancer Water Repellent Specification

Specifier Note: The information provided below is intended to guide the Architect in developing specifications for products manufactured by PROSOCO, Inc. and should not be viewed as a complete source of information about the product(s). The Architect should always refer to the Product Data Sheet and MSDS for additional recommendations and for safety information. See also PROSOCO Section 07190 Water Repellents.

Specifier Note: Paragraph below is for PART 1 GENERAL, Quality Assurance.

Test Area

Test a minimum 4 ft. by 4 ft. area on each type of masonry. Use the manufacturer's application instructions. Let test area protective treatment cure before inspection. Keep test panels available for comparison throughout the protective treatment project.

Specifier Note: Paragraphs below are for PART 2 PRODUCTS, Manufacturers and Products.

Manufacturer: PROSOCO, Inc., 3741 Greenway Circle, Lawrence, KS 66046. Phone: (800) 255-4255; Fax: (785) 830-9797. E-mail: CustomerCare@prosoco.com

Product Description

Sure Klean[®] Paver Enhancer is a solvent-based blend of high-quality siloxanes modified to provide excellent water repellency and color enhancement to interlocking concrete, fired clay, porous tile and many types of natural stone surfaces. Paver Enhancer penetrates and reacts with the surface to form a chemical bond, providing long-term durability, alkali resistance and superior breathability.

Technical Data

ACTIVE CONTENT: 20%

FORM: Clear liquid, mild petroleum odor

SPECIFIC GRAVITY: 0.871

FLASH POINT: 102 degrees F (39 degrees C) (ASTM D 3278)

FREEZE POINT: <-22 degrees F (<-30 degrees C)

WT./GAL.: 7.25 lbs.

VOC Content = 693 g/L

Limitations

- Not suitable for extremely dense or asphaltic surfaces.
- Not recommended for below-grade applications.
- Will not prevent water penetration through structural cracks, defects or open joints.

Specifier Note: Paragraphs below are for PART 3 EXECUTION, Installation.

Application

Before applying, read "Protect" and "Precautionary Measures" sections in the Manufacturer's Product Data Sheet for Paver Enhancer. Refer to the Product Data Sheet for additional information about application of Paver Enhancer. Do not dilute or alter.

Spray Application (Vertical)

1. For best results, apply protective treatment" to a visibly dry and absorbent surface.
2. Thoroughly saturate the surface. Use enough for a rundown of 6" to 8" below the spray pattern.
3. Brush out heavy runs and drips.

Spray Application (Horizontal)

1. For best results, apply protective treatment to a visibly dry and absorbent surface.
2. Thoroughly saturate the surface for 2 to 3 minutes before penetrating. Lightly broom out puddles. Use clean absorbent towels to pick up excess material that doesn't immediately penetrate.

Brush or roller: Saturate the surface uniformly. Avoid excessive overlapping. Brush out heavy runs and drips to avoid buildup.

Second Coat Application

Some highly porous surfaces may need 2 applications for uniform color enhancement. Apply the second application when the first coat is dry to touch.

Note: On dense natural stone, use a soft cloth or lamb's wool. Let protective treatment penetrate for 2 to 5 minutes. Wipe up excess.