

Paramastic™

Accessory to Paraseal®

S

Product Description:
Paramastic is an expandable mastic and caulk for use with Paraseal waterproofing membrane.

Basic Uses:
To protect against water leakage in the areas of: penetration, honeycombs, unfilled ties or spalled concrete. Paramastic is an important part of the Paraseal waterproofing system- substitutions are not allowed.

Materials:
A thick paste containing expandable bentonite designed to be applied over dry, damp, frozen or uncured concrete. Product reacts to and stiffens in the presence of water to form an impervious membrane.

Packaging:
2 gallon (7.57 L) and 5 gallon (19.1 L) pails.

Limitations:

- Do not apply in standing water or over ice and snow.

INSTALLATION
Preparatory Work:
For good adhesion, the surface must be sound, clean, dry and free of all dirt, dust and oil. Trowel over honeycombs deeper than 1/4" (6.4mm) Fill all tie holes and spalled areas prior to the installation of Paraseal.

General:
Always cover Paramastic with a protective layer of Paraseal membrane. All vertical inside corners receive a cove detail of Paramastic.

Penetrations:
Place 1" (25 mm) cove around all penetrations and extend 1.5" (37.7 mm) beyond.

Lagging:
Apply Paramastic around all tiebacks and penetrations. Protect with 4 mil polyethylene or a protective layer of Paraseal LG.

Storage:
Paramastic will not react to air however, care must be taken to prevent water contamination in container.

Availability:
Immediately available from your

local Tremco Field Representative, Tremco Distributor or Tremco Warehouse.

Warranty:
Tremco warrants its Paraseal Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Paraseal Products. Tremco's sole obligation shall be, at its option, to replace, or refund the purchase of the quantity of Paraseal Products proved to be defective and Tremco shall not be liable for any loss or damage including incidental or consequential damages arising from the use of Paraseal Products.

TECHNICAL DATA

Physical Property

Physical Property	Value
Color	Gray/Black
Resistance to Micro-organisms (bacteria, fungi, mold, yeast)	Unaffected
Resistance to water migration	100%
Co-efficient of permeability	1.0 x 10-9
Freeze/Thaw cycle (-15°F/-26°C)	Unaffected
Rain resistance	48 hours
Fiber or filler	0%
Flash Point	Approx. 346°F (174°C)
Specific Gravity	1.2
Weight	Approx. 10 lbs. gal.

For MSDS and Spec Data Sheets,
Call our 24 Hour Fax-Back Line:

1-800-551-2806

or visit our website:

www.tremcosealants.com

TREMCO INCORPORATED

Sealant/Weatherproofing Division
Tremco • Mameco/Vulkem® • Paramount

3735 Green Road • Beachwood, Ohio • 44122 • Phone: (216) 292-5000 • (800) 321-7906
220 Wicksteed Avenue • Toronto, ON M4H 1G7 • Phone: (416) 421-3300 • (800) 363-3213

TREMCO
VULKEM • PARASEAL