

Paraseal® Accessories

S

Paraseal Paraterm Bar™

An aluminum alloy specially formulated to exhibit excellent holding power. When fastened through pre-cut holes, Paraterm Bar provides tight, straight and extremely long lived terminations, caulk troughs and drip edges.

Packaging: shipped in bundles of 50, approx. 500 linear feet (152m).

Para JT™

An adhesive joint tape compound formulated with cross-linked polymeric elastomers. When used with Paraseal GM, it creates double seals on all joints forming two complete and independent waterproofing systems. When used with Paraseal GM, it forms a natural gas and waterproof joint. Para JT is utilized with Paraseal LG membrane in vaporproofing installations for effectively sealing around penetrations.

Packaging: 1/8" x 2" x 25' (0.3cm x 5.1cm x 7.6cm)/ 12 rolls per carton.

Temporary Tape™

A composite of acrylic adhesive bonded to polyvinyl chloride coated fabric. The tape is a temporary joint closure tape used to protect the joints of the installed Paraseal membrane against debris intrusion during backfill and damage from rain. The tape is also used to temporarily terminate the Paraseal to the substrate and hold insulation in place prior to backfill.

Temporary Tape requires Paraprimer when applied to concrete and masonry.

Packaging: (4) 3" x 180' roll per box = 720 ft (219m).

Permanent Seam Tape™

Consists of a 4" wide x 60 mil thick (100mm x 1.5mm) rubberized asphalt membrane laminated to a polyethylene reinforcing film. A removable release paper protects the adhesive membrane face until removed during installation. Permanent Seam Tape is used primarily for sealing the seams of Paraseal and Deckseal applications when flood testing is desired. It is used on all seams of Saltwater Paraseal applications and with Paraseal LG when installed for vaporproofing. The inherent adhesive and waterproofing properties of the rubberized-asphalt membrane effectively seals the HDPE (High Density Polyethylene) liner face or Paraseal products to render the bentonite a secondary back-up.

Packaging: 75' long rolls (22m)/ 6 rolls per case.

Paraprimer®

An adhesive primer formulated to prepare construction surfaces prior to application of Parastick 'n' Dry, Superstop and various tapes. Construction surfaces other than HDPE (High Density Polyethylene) liner are always primed with Paraprimer prior to taping. Paraprimer helps create a bonding to any sound, clean surface and to provide a flexible base to enhance adhesion.

Packaging: 1 gallon pail (3.75 l).

Approximate Coverage per Gallon

Metal = 150-300 sq ft/gallon (4-10m²/ l)

Concrete = 100-300 sq ft/gallon (2.6-10m²/ l)

Wood = 100-300 sq ft/gallon (2.6-10m²/ l)

Paragranular®

A premium, Wyoming type, high swelling, granular, sodium bentonite. When in the presence of water, Paragranular reacts and forms an impervious waterproof gel. Paragranular is designed to work in conjunction with Paraseal products to form a waterproof transitional seal. It is used to form a cove at all horizontal to vertical transition, at floor/wall transitions and penetrations through horizontal surfaces, and to fill voids around irregularities.

Packaging: 50 lbs. (22.7 Kg) bags

Paramastic™

An expandable mastic for use with Paraseal waterproofing membrane. Paramastic is used to protect against water leakage in the areas of: penetration, honeycombs, unfilled ties or spalled concrete.

Packaging: 2 (7.57 l) and 5 (18.9 l) gallon pails

Parastick 'n' Dry®

A laminate of bentonite applied to mesh with a pressure sensitive adhesive on one side. Parastick 'n' Dry is used in conjunction with waterstops Parastop II, waterproofing membranes, Paraseal and Paramastic to assist in waterproofing difficult areas. It is used in blindside waterproofing applications to detail soldier piles and to wrap concrete imbeds such as pipe penetrations. Parastick 'n' Dry can also be used to form water isolations such as in sandwich-slab applications.

Packaging: (12) 15 foot, 1" wide (4.6m/2.54cm) rolls per carton, (4) 25 foot, 3" wide (7.6 m/7.6 cm) rolls per carton, (2) 50 foot, 6" wide (15.3 m/15.3cm) rolls per carton.



Availability:

Immediately available from your local Tremco Field Representative, Tremco Distributor or Tremco Warehouse.

Warranty:

Tremco warrants its Paraseal Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and

on site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Paraseal Products. Tremco's sole obligation shall be, at its option, to replace, or refund the purchase of the quantity of Tremco Paraseal Products proved to be defective and Tremco shall not be liable for any loss or damage.

For MSDS and Spec Data Sheets,
Call our 24 Hour Fax-Back Line:
1-800-551-2806
or visit our website:
www.tremcosealants.com

TREMCO INCORPORATED
Sealant/Weatherproofing Division

3735 Green Road • Beachwood, Ohio • 44122 • Phone: (216) 292-5000 • (800) 321-7906
220 Wicksteed Avenue • Toronto, ON M4H 1G7 • Phone: (416) 421-3300 • (800) 363-3213